



TECHNICAL DATA SHEET

LB-3000

Natural-Based, Moderate-Duty Metalworking Lubricant

DESCRIPTION

LB-3000 is a quality moderate-duty metalworking lubricant for general machining and woodworking operations. It is manufactured using renewable raw materials and is non-toxic and biodegradable. Cleaning required before heat treating.

APPLICATIONS

- Moderate-duty operations
- Replace "mist" lubricant/coolant
- Lumber and woodworking operations

MATERIALS COMPATIBILITY

- Recommended for ferrous and nonferrous metals

PHYSICAL PROPERTIES

<i>Appearance</i>	Dark blue fluid
<i>Specific Gravity</i>	0.92
<i>Density</i>	7.7 lbs/gal (922 kg/m ³)
<i>Viscosity at 40°C</i>	37 cSt
<i>Flash Point</i>	608°F (320°C)
<i>Pour Point</i>	-4°F (-20°C)
<i>Pin & Vee Block</i>	1500 lbs)
<i>Sulfur</i>	None
<i>Chlorine</i>	None
<i>Silicones</i>	None
<i>Mineral Oil</i>	0%
<i>Water Solubility</i>	Insoluble

AVAILABLE IN

1 gal.....	LB3000
55 gal.....	LB3055

HEALTH AND SAFETY

This product is made from renewable raw materials and is naturally non-toxic. For complete health and safety information refer to product MSDS (Material Safety Data Sheet) on our web site at www.rocolnorthamerica.com.

For additional information please contact our Customer Service Department at 800-452-5823 ext. 2.