

Non-Silicone Defoamer

DESCRIPTION

Non-Silicone Defoamer minimizes and controls foaming in all types of metalworking fluids and no cleaning is required before painting or plating.

APPLICATIONS

- Minimize and control foaming in water-miscible metalworking fluids

MATERIALS COMPATIBILITY

- Recommended for ferrous and nonferrous metals

PHYSICAL PROPERTIES

<i>Concentrate Color</i>	Opaque white
<i>pH</i>	8.5
<i>Specific Gravity</i>	1.05
<i>Density</i>	8.7 lbs/gal (1041 kg/m ³)
<i>Flash Point</i>	400°F (204°C)
<i>Boiling Point</i>	> 200°F (93°C)
<i>Chlorine</i>	None
<i>VOCs</i>	Nil
<i>Mineral Oil</i>	0%

DILUTION RATIOS

- Water-Soluble Oils.....1 oz Defoamer to 30 gal water
- Semi-Synthetic Metalworking Fluids.....1 oz Defoamer to 75 gal water
- Synthetic Metalworking Fluids.....1 oz Defoamer to 300 gal water

AVAILABLE IN

1 gal..... 78640

HEALTH AND SAFETY

Refer to MSDS (Material Safety Data Sheet) for complete information on health and safety on our web site at www.rocolnorthamerica.com.

For additional information please contact our Customer Service Department at 800-452-5823 ext. 2.

Revision: July 29, 2008