



# TECHNICAL DATA SHEET

## 606

Moisture-absorbing long-term rust preventative

### DESCRIPTION

606 is a moisture-absorbing rust preventative with two-year indoor corrosion protection. It can be used on wet parts and protects against corrosion with a thin oily-film.

### APPLICATIONS

For corrosion and rust prevention  
Apply by brushing or dipping

### MATERIALS COMPATIBILITY

Recommended for ferrous and nonferrous metals

### PHYSICAL PROPERTIES

*Color*.....Red-brown  
*Specific Gravity* .....0.83  
*Density* .....6.9 lbs/gal (830 kg/m<sup>3</sup>)  
*Flash Point*.....175°F (79°C)  
*Boiling Point*.....> 212°F (100°C)  
*Chlorine*.....None  
*VOCs*.....72%  
*Mineral Oil*.....28%

### DILUTION RATIOS

DO NOT DILUTE

### AVAILABLE SIZES

*1 gallon (4/case)* .....71152  
*5 gallon*.....71052  
*55 gallons*.....71552

### HEALTH AND SAFETY

Use proper safety equipment. Avoid contact with skin, eyes, and clothes. Avoid inhaling vapor or mist. Keep away from extreme heat. Keep container closed when not in use. For complete Health and Safety Information refer to product Material Safety Data Sheet (MSDS) which can be downloaded at [www.rocolnorthamerica.com/msds.htm](http://www.rocolnorthamerica.com/msds.htm).

For more information contact 800-452-5823 x2 or visit [www.rocolnorthamerica.com](http://www.rocolnorthamerica.com).

The information in this document is believed to be accurate at the date of issue. Because conditions of use are beyond manufacturer's control no guarantee or warranty is expressed or implied.