

Rustlick PowerChip 2000

Biostable Heavy-Duty Synthetic Coolant

(Revision: December 12, 2003)

APPLICATIONS

- Heavy-duty machining, grinding and sawing of all metals.
- Exceptional biostability provides long-term sump life when properly maintained.
- Non-chlorinated EP package provides extended tool life.
- Works well in hard-water environments.
- Transparent solution allows for easy viewing of workpiece.
- Provides excellent rust protection and minimal foaming.
- Provides superior way-lube rejection, leading to cleaner coolant and longer sump life.

MATERIALS COMPATIBILITY

- Good for ferrous metals especially titanium, inconel, stainless steel.
- Provides excellent rust protection.
- Suited for hard to machine aluminum and other alloys.

AVAILABLE IN:

5 Gallon: 76305
55 Gallon: 76355

DILUTION RATIO

- 10:1 up to 30:1, depending on application

HEALTH AND SAFETY

- Refer to MSDS (Material Safety Data Sheet) for complete information on health and safety.

For MSDS
visit our website at
www.rocolnorthamerica.com

PHYSICAL PROPERTIES

Appearance: Concentrate:	Transparent dark blue
Diluted:	Transparent bright blue
pH @ 5% dilution:	9.5
Refractometer reading:	10:1 = 4.0 20:1 = 2.0 30:1 = 1.2
Specific gravity (conc):	1.07
Density (concentrate):	8.88 lbs./gallon
Total chlorine:	0.0%
Flash Point:	None
Boiling Point:	212°F
Mineral Oil Content:	0.0%

