

## **TECHNICAL DATA SHEET**

## WS-1000 / PowerCool

Water-soluble oil metalworking fluid concentrate

**DESCRIPTION** WS-1000 is a water-soluble oil cutting & grinding fluid with chlorinated extreme-pressure

additives for moderate to heavy-duty general machining with ferrous and nonferrous

metals.

**APPLICATIONS**Moderate to heavy-duty machining and grinding

MATERIALS COMPATIBILITY Recommended for ferrous/nonferrous metals, aluminum, brass, bronze, and copper.

Limited use on titanium.

Dilute Color ......Milky white

Odor......Mild, characteristic

 Chlorine
 4.1%

 Mineral Oil
 58%

Refractometer Index (% Brix) ......10:1 (10%) = 9.4

20:1 (5%) = 4.7

30:1 (3%) = 3.2

**DILUTION RATIOS**These dilution ratios are meant to be used only as general guidelines and are not

considered exact specifications. Please contact your Rustlick Sales Representative for an

exact application concentration recommendation.

 Light-duty machining
 30:1 (3%)

 Moderate-duty machining
 20:1 (5%)

 Heavy-duty machining
 10:1 (10%)

**AVAILABLE SIZES** *5 gallon; net weight 43 lbs (19.5 kg).....* 82205

55 gallons; net weight 480 lbs (218 kg) ......82255

**HEALTH AND SAFETY** Use proper safety equipment. Avoid contact with skin, eyes, and clothes. Avoid inhaling

vapor or mist. Keep away from extreme heat. Keep container closed when not in use. For complete Health and Safety information refer to product Material Safety Data Sheet (MSDS). Product MSDS can be downloaded from www.rocolnorthamerica.com/msds.htm

For more information contact 800-452-5823 ext. 2. or visit www.rocolnorthamerica.com

The information in this document is believed to be accurate at the date of issue. Because conditions of use are beyond manufacturer's control no guarantee or warranty is expressed or implied.

Effective Date: 07/30/2010